

## DS-2CE72DFT-PIRXOF 2 MP PIR Siren Full Time Color Camera



ColorVu



- 2 MP, 1920 × 1080 resolution
- 24-hour color image
- 130 dB true WDR, 3D DNR
- 3.6 mm, 6 mm fixed focal lens
- Smart Light, up to 20 m white light distance
- PIR detection, strobe light alarm, alarm out/audible alarm
- Built-in siren
- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)
- IP67



## Specification


| Camera                            |   |
|-----------------------------------|---|
| Image Sensor                      | 2 MP CMOS   |
| Signal System                     | PAL/NTSC  |
| Resolution                        | 1920 (H) × 1080 (V)   |
| Frame Rate                        | TVI: 1080p@30fps, 1080p@25fps<br>AHD: 1080p@30fps, 1080p@25fps<br>CVI: 1080p@30fps, 1080p@25fps<br>CVBS: PAL/NTSC |
| Min. illumination                 | Color: 0.0005 Lux @ (F1.0, AGC ON), 0 Lux with white light  |
| Shutter Time                      | PAL: 1/25 s to 1/50, 000 s<br>NTSC: 1/30 s to 1/50, 000 s   |
| Slow Shutter                      | Max. 16 times   |
| Lens                              | 3.6 mm, 6 mm fixed lens   |
| Horizontal Field of View          | 83.6° (3.6 mm), 52.8° (6 mm)  |
| Lens Mount                        | M16   |
| Flashing Light Alarm (Red & Blue) | Yes   |
| Audible Alarm                     | Yes   |
| Day & Night                       | Color   |
| WDR (Wide Dynamic Range)          | ≥130 dB   |
| Angle Adjustment                  | Pan: 0 to 360°, Tilt: 0 to 75°, Rotation: 0 to 360°   |
| Menu                              |   |
| White Light                       | AUTO/OFF  |
| Image Mode                        | STD/HIGH-SAT  |
| AGC                               | Yes   |
| White Balance                     | Auto/Manual   |
| AE (Auto Exposure) Mode           | WDR/BLC/HLC/Global/HLS  |
| Anti-Banding                      | Yes   |
| Privacy Mask                      | 4 programmable privacy masks  |
| Motion Detection                  | 4 programmable motion areas   |
| Noise Reduction                   | 3D DNR/ 2D DNR  |
| Language                          | English   |
| Function                          | Brightness, Sharpness, Mirror, Smart Light, Defective Pixel Correction  |
| Interface                         |   |
| Video Output                      | Switchable TVI/AHD/CVI/CVBS   |
| Alarm                             | 1 alarm out   |

| General              |  |
|----------------------|--|
| Operating Conditions | -40 °C to 60 °C (-40 °F to 140 °F), humidity 90% or less (non-condensing)                                |
| Power Supply         | 12 VDC ± 25%<br><i>*You are recommended to use one power adapter to supply the power for one camera.</i> |
| Power Consumption    | Max. 6.6 W   |
| Protection Level     | IP67   |
| Material             | Enclosure: Plastic<br>Main Body: Metal   |
| White Light Range    | Up to 20 m   |
| PIR Range            | Angle: 110°, Range: 11 m   |
| Communication        | HIKVISION-C  |
| Dimensions           | Φ 109.82 mm × 93.66 mm (Φ 4.32" × 3.7")  |
| Weight               | Approx. 390 g (0.86 lb.)   |


### Available Model

DS-2CE72DFT-PIRXOF

### Dimension



### Accessory





**DS-1272ZJ-110-TRS**  
Wall Mount

**DS-1275ZJ-SUS**  
Vertical Pole Mount

**DS-1276ZJ-SUS**  
Corner Mount

**DS-1281ZJ-S**  
Inclined Ceiling Mount



**DS-1280ZJ-S  
Junction Box**

**DS-1280ZJ-TR13  
Junction Box**

Distributed by



**HIKVISION®**

**Headquarters**

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
overseasbusiness@hikvision.com

**Hikvision USA**  
T +1-909-895-0400  
sales.usa@hikvision.com

**Hikvision Australia**  
T +61-2-8599-4233  
salesau@hikvision.com

**Hikvision India**  
T +91-22-28469900  
sales@pramahikvision.com

**Hikvision Canada**  
T +1-866-200-6690  
sales.canada@hikvision.com

**Hikvision Thailand**  
T +662-275-9949  
sales.thailand@hikvision.com

**Hikvision Europe**  
T +31-23-5542770  
sales.eu@hikvision.com

**Hikvision Italy**  
T +39-0438-6902  
info.it@hikvision.com

**Hikvision Brazil**  
T +55 11 3318-0050  
Latam.support@hikvision.com

**Hikvision Turkey**  
T +90 [216]521 7070- 7074  
sales.tr@hikvision.com

**Hikvision Malaysia**  
T +601-7652-2413  
sales.my@hikvision.com

**Hikvision UK & Ireland**  
T +01628-902140  
sales.uk@hikvision.com

**Hikvision South Africa**  
Tel: +27 (10) 0351172  
sale.africa@hikvision.com

**Hikvision France**  
T +33(0)1-85-330-450  
info.fr@hikvision.com

**Hikvision Kazakhstan**  
T +7-727-9730667  
nikia.panfilov@hikvision.ru

**Hikvision Vietnam**  
T +84-974270888  
sales.vt@hikvision.com

**Hikvision UAE**  
T +971-4-4432090  
salesme@hikvision.com

**Hikvision Singapore**  
T +65-6684-4718  
sg@hikvision.com

**Hikvision Spain**  
T +34-91-737-16-55  
info.es@hikvision.com

**Hikvision Tashkent**  
T +99-87-1238-9438  
uzb@hikvision.ru

**Hikvision Hong Kong**  
T +852-2151-1761  
info.hk@hikvision.com

**Hikvision Russia**  
T +7-495-669-67-99  
saleru@hikvision.com

**Hikvision Korea**  
T +82-(0)31-731-8817  
sales.korea@hikvision.com

**Hikvision Poland**  
T +48-22-460-01-50  
info.pl@hikvision.com

**Hikvision Indonesia**  
T +62-21-2933759  
Sales.Indonesia@hikvision.com

**Hikvision Colombia**  
sales.colombia@hikvision.com