

## SWITCH-8P



### SPECIFICATIONS

<b>Model Number</b>	SWITCH-8P
<b>Interface</b>	
<b>Downlink ports</b>	1-8 : 10/100Mbps RJ45 Ports
<b>Uplink port</b>	9 : 10/100Mbps RJ45 Ports
<b>PoE / Power Supply</b>	
<b>MAX PoE output</b>	30W
<b>Total power supply</b>	96W
<b>Priority Function</b>	Support
<b>LEDs</b>	
<b>LEDs</b>	Link/activity
<b>Transfer Method</b>	
<b>Transfer Method</b>	Store-and-forward
<b>Advanced Feature</b>	
<b>Advanced Feature</b>	IEEE802.3x Flow control for full- Duplex mode and Backpressure for Half-Duplex mode
<b>Performance</b>	
<b>Switching Capacity</b>	1.8Gbps
<b>Packet Forwarding Rate</b>	1.34Mbps
<b>Mac Address Table</b>	4K
<b>Standards and Protocols</b>	
<b>Standards and Protocols</b>	IEEE802.3i 10 BASE-T
<b>Standards and Protocols</b>	IEEE802.3u 100 BASE-TX
<b>Standards and Protocols</b>	IEEE802.3x Flow Control
<b>Standards and Protocols</b>	IEEE802.3af Power over Ethernet
<b>Standards and Protocols</b>	IEEE802.3at Power over Ethernet
<b>Standards and Protocols</b>	IEEE802.3az EEE

## General

<b>Power Input</b>	AC 100-240V 50/60Hz
<b>Dimensions</b>	200mm(L) *118mm(W) *44mm(H)
<b>Cables</b>	UTP category 5 or above cable
<b>Operating Temperature</b>	0 – 45 °C
<b>Storage Temperature</b>	-10 – 70 °C
<b>Operating Humidity</b>	90% max relative humidity, on-condensing
<b>Storage Humidity</b>	90% max relative humidity, on-condensing

## DIP Switch mode

<b>VLAN</b>	It comes along with VLAN features and each PoE port can only communicate with Uplink.
<b>Video</b>	Improve the phenomenon of stuttering and mosaic in the monitoring network.
<b>Switch</b>	It can be used as normal Switch features

## SPECIFICATIONS

<b>Model Number</b>	SWITCH-8P
<b>Interface</b>	
<b>Downlink ports</b>	1-8 : 10/100Mbps RJ45 Ports
<b>Uplink port</b>	9 : 10/100Mbps RJ45 Ports
<b>PoE / Power Supply</b>	
<b>MAX PoE output</b>	30W
<b>Total power supply</b>	96W
<b>Priority Function</b>	Support
<b>LEDs</b>	
<b>LEDs</b>	Link/activity

<b>Transfer Method</b>	
<b>Transfer Method</b>	Store-and-forward
<b>Advanced Feature</b>	
<b>Advanced Feature</b>	IEEE802.3x Flow control for full-Duplex mode and Backpressure for Half-Duplex mode
<b>Performance</b>	
<b>Switching Capacity</b>	1.8Gbps
<b>Packet Forwarding Rate</b>	1.34Mbps
<b>Mac Address Table</b>	4K
<b>Standards and Protocols</b>	
<b>Standards and Protocols</b>	IEEE802.3i 10 BASE-T
	IEEE802.3u 100 BASE-TX
	IEEE802.3x Flow Control
	IEEE802.3af Power over Ethernet
	IEEE802.3at Power over Ethernet
	IEEE802.3az EEE

