

## VI-POESWITCH-4



### Key Features:

- Layer two commercial switch.
- Supports IEEE802.3, IEEE802.3u and IEEE802.3X standards.
- MAC auto study and aging, MAC address capacity is 1K.
- RJ45 port supports 10/100 Mbps self-adaptation, supports IEEE802.3af and IEEE802.3at power supply standards.
- Supports MDI/MDIX self-adaptation.
- Metal enclosure.
- Supports DC 48V-57V power supply.
- Supports wall-mount installation.
- Supports anti-theft lock hole.

### SPECIFICATIONS

<b>Model Number</b>	VI-POESWITCH-4
<b>Ethernet Port</b>	1*10/100 Base-T 4*10/100 Base-T (PoE power supply) Embedded LINUX
<b>PoE Power Consumption</b>	Port1 ≤60W, Port 2-4≤30W, Total ≤60W
<b>PoE PIN Assignment</b>	1, 2, 4, 5 (V+), 3, 6, 7, 8 (V-)
<b>PoE Power Management</b>	Support
<b>PoE Protocol</b>	IEEE802.3af (PoE), IEEE802.3at (PoE+), Hi-PoE
<b>Switching Capacity</b>	1Gbps
<b>Packet Forwarding Rate</b>	744Kpps
<b>Packet Buffer Memory</b>	448Kb
<b>MAC Table Size</b>	1K
<b>Flow Control</b>	Enable
<b>Application Humidity</b>	5% ~ 95%
<b>Power</b>	DC48~57V power adapter
<b>Lightning Protection</b>	Common Mode 2KV Differential Mode 1KV
<b>ESD Protection</b>	Air Discharge 8KV Contact Discharge 6KV
<b>Working Temperature</b>	-10°C ~55°C
<b>Weight</b>	290g
<b>Dimension(W×D×H)</b>	130mm × 85mm × 26mm